



Device type: **ASP-200**

Outdoor Siren

Outdoor signalling device with a loud sound will draw the attention of neighbours and passers-by, and sometimes even discourage intruders, from entering the property. Designed for mounting on the building facade, e.g. from the street side.

- optical (LED) and acoustic signalling
- operation in the 868 MHz frequency band
- AES encrypted two-way radio communication
- transmission channel diversity – 4 channels for automatic selection of the one that will enable transmission without interference with other signals
- remote settings programming
- remote firmware update
- battery status control
- tamper protection against enclosure opening and removal from mounting surface
- built-in spirit level facilitating installation
- durable housing resistant to mechanical damage
- weatherproofed electronic circuit
- temperature operating range: $-40^{\circ}\text{C} \div +55^{\circ}\text{C}$
- compliance with EN 50131 Grade 2



Operating frequency band	868.0 MHz ÷ 868.6 MHz
Battery	ER34615 3.6 V
Battery life expectancy	up to 2.5 years
Standby current consumption	650 µA
Sound pressure level (at 1 m distance).....	up to 105 dB
Complied with standards.....	EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-4, EN 50131-5-3
Security grade according to EN 50131-1	Grade 2
Environmental class according to EN 50130-5	IIIA
Operating temperature range	-40°C ...+55°C
Maximum humidity.....	93±3%
Dimensions	148 x 254 x 64 mm
Weight	762 g



Compatible with
abox2
wireless system

ASP-200